What is claimed is:

Claims

1. A method for maintaining SIP contact addresses:

10

15

20

sending, by a SIP proxy user agent (UA), a first registration message for a remote unit to a SIP registrar;

sending a second registration message for the remote unit to the SIP registrar;

receiving, in response to the second registration message, a response that indicates a contact address more recent than any provided by the SIP proxy UA; and

sending, in response to the received response, a deregistration message for the remote unit to the SIP registrar.

- 2. The method of claim 1 further comprising receiving, by the SIP proxy UA, a non-SIP registration request from the remote unit prior to sending the first registration message.
 - 3. The method of claim 1 wherein the second registration message is sent in response to a registration timer expiration.
 - 4. The method of claim 1 wherein the first registration message comprises a SIP REGISTER message.
- 5. The method of claim 4 wherein the SIP REGISTER message25 indicates that it comprises a new contact address.
 - 6. The method of claim 1 wherein the second registration message comprises a SIP REGISTER message.

- 7. The method of claim 1 wherein the response that indicates a contact address more recent than any provided by the SIP proxy UA comprises a SIP 200 OK message and at least one creation time stamp.
- 5 8. The method of claim 7 wherein the response further comprises a group of contact addresses and a creation time stamp for each.
 - 9. The method of claim 1 wherein the deregistration message comprises a SIP REGISTER message with an Expires header value of "0".

10

A method for maintaining SIP contact addresses:

receiving a first registration message for a remote unit from a first SIP proxy user agent (UA);

storing, as a member of a group of contact addresses for the remote unit, both a first contact address based on the first registration message and a first creation timestamp for the first contact address;

receiving a second registration message for the remote unit from a second SIP proxy UA after receiving the first registration message;

storing, as a member of the group of contact addresses for the remote unit, both a second contact address for the remote unit and a second creation timestamp for the second contact address;

receiving a third registration message for the remote unit from the first SIP proxy UA;

sending, in response to the third registration message, a response that indicates a contact address more recent than any provided by the first SIP proxy UA;

receiving a deregistration message for the remote unit from the first SIP proxy UA; and

removing, from the group of contact addresses for the remote unit, the first contact address.

- 11. The method of claim 10 wherein the response that indicates a contact address more recent than any provided by the first SIP proxy UA comprises a SIP 200 OK message and at least one creation time stamp.
- 12. The method of claim 11 wherein the response further comprises a group of contact addresses and a creation time stamp for each.

25

20

5

10

15

13. The method of claim 10 wherein the first registration message comprises a SIP REGISTER message, the second registration message comprises a SIP REGISTER message, and the third registration message comprises a SIP REGISTER message.

5

14. The method of claim 10 wherein the deregistration message comprises a SIP REGISTER message with an Expires header value of "0".

- 15. A radio access network (RAN) component comprising:
- a wireless network interface; and

5

- a SIP proxy user agent, communicatively coupled to the wireless network interface, adapted to
- receive a registration request from a remote unit via the wireless network interface,
- send a first registration message for the remote unit to a SIP registrar,
- send a second registration message for the remote unit to the SIP registrar,
 - receive, in response to the second registration message, a response that indicates a contact address more recent than any provided by the SIP proxy UA, and
- send, in response to the received response, a deregistration message for the remote unit to the SIP registrar.

16. A SIP registrar comprising:

a SIP location data base; and

5

10

15

20

25

a SIP location processor, communicatively coupled to the SIP registration data base, adapted to

receive a first registration message for a remote unit from a first SIP proxy user agent (UA),

store in the SIP location data base, as a member of a group of contact addresses for the remote unit, both a first contact address based on the first registration message and a first creation timestamp for the first contact address,

receiving a second registration message for the remote unit from a second SIP proxy UA after receiving the first registration message,

storing in the SIP location data base, as a member of the group of contact addresses for the remote unit, both a second contact address for the remote unit and a second creation timestamp for the second contact address.

receiving a third registration message for the remote unit from the first SIP proxy UA,

sending, in response to the third registration message, a response that indicates a contact address more recent than any provided by the first SIP proxy UA,

receiving a deregistration message for the remote unit from the first SIP proxy UA, and

removing, from the group of contact addresses for the remote unit, the first contact address.